



DECO MINI - glitter paint additive

The **REVCO DECO GLITTER MINI** is ideal for making exterior or interior surfaces to be painted glittery at the same time as they are being painted. The **additive DECO GLITTER MINI** should be mixed well into the wall paint **REVCO ALFA, EXTERIOR** or **SILICON**, which has already been mixed to the colour chosen, and applied to the surface in the usual manner. Upon drying, indoors, it reaches the desired effect with a strong lighting, while outdoors, the discreet silvery glitter effect reveals itself in sunlight.

For 1 bucket (10/15 litres) of the wall paint **REVCO ALFA, EXTERIOR** or **SILICON**, 1 jar (120 g) of the **glitter additive REVCO DECO MINI** is recommended.

DECO MAX - glitter plaster additive

Mixed with the plaster **REVCO NEO+, VARIO** or **SILICON**, the **glitter additive REVCO DECO GLITTER MAX** is suitable for decorating the exterior facade or the internal walls of old and new buildings with glitter effect. The surface thus created does not glitter on its own, the spectacular appearance fully reveals itself upon application and drying, in sunshine or intense artificial lighting.

For 1 bucket (15 kg) of the thin plaster **REVCO NEO+, VARIO** or **SILICON**, 1 jar (120 g) of the **glitter additive REVCO DECO MAX** is recommended.

PROPERTIES OF THE SUBSTRATE

The substrate should have the same properties as those given for the basic paint / base plaster intended for use.

PREPARATION AND PRIMING

The preparations and the priming to be carried out are the same as those for the basic paint / base plaster intended for use.

APPLICATION

Application tool: It is the same as that for the basic paint / base plaster intended for use.

Method of application: It is the same as that for the basic paint / base plaster intended for use.

TECHNICAL DATA:

Material requirement:

For **REVCO DECO GLITTER MINI**: 1 jar (120 g) of glitter additive per 1 bucket (10/15 litres) of paint is recommended.

For **REVCO DECO GLITTER MAX**: 1 jar (120 g) of glitter additive per 1 bucket (15 kg) of plaster is recommended.

Application temperature: During application and drying, the temperature of both the air and the wall surface must be between +5°C and +25°C.

Surface drying time: It is the same as that for the basic paint / base plaster intended for use.

Total drying time: It is the same as that for the

basic paint / base plaster intended for use.

Suitability for repainting and repairing: The glittery surface can be later repainted with the **facade paint REVCO EXTERIOR**.

The values given are valid at 20°C temperature and 42% relative humidity. As the weather changes, with lower temperatures and higher humidity, the drying times become longer, with higher temperatures and lower humidity, the drying times become shorter.

Storage life: In original, unopened packaging in a dry place, the glitter additive may be stored indefinitely; it is not frost-sensitive.

Packaging: 120 g

INFORMATION:

While drying, the agent must be protected from direct sunlight, draught, frost, driving rain, and temperatures above 25°C. Please refer to the technical information before application. Our technical specification is based on the premise that our products are used by trained professionals. The product and the information leaflet have been produced on the basis of our latest experience and knowledge, but this does not exempt the user from carrying out preliminary practical tests and colour checks. After starting the application, no complaints with respect to colour shall be accepted.

Avoid contact with skin and eyes; in case of contact, rinse thoroughly with water and consult a doctor if necessary.